



WJ-NV200 CATALOG

Features

- H.264, MPEG-4 and JPEG multi format
 - Up to 16 network cameras can be connected and recorded.
 - Quick setup by automatic camera detection and simple setup wizard without the use of PC
 - "Referenced recording days" is automatically calculated by frame rate, image quality and HDD capacity.
 - Simple mouse operation by new GUI without the use of PC
 - Quick intuitive search with calendar and timeline
 - Live images from up to 16 cameras can be displayed simultaneously.
 - Supports the Full HD output (HDMI) that can display recorded images and live images in high definition
 - Real Time Face Matching function by matching registered face images with a face displayed on live images * Only channel 1 * Cameras supporting face detection function is required. (WV-NP502, WV-SP305, or WV-SP306 is recommended.)
 - Face matching alarm is notified by Buzzer / E-mail / Panasonic alarm / Terminal output / Indicator.
 - Various alarm sources include 9x Terminal inputs, 16x Camera alarm, Panasonic Alarm Protocol. Flexible alarm actions include Alarm recording, E-mail notification, Alarm message, Camera positioning, Terminal output, Panasonic alarm protocol output, Buzzer and Indicator.
 - Camera Control: Pan/Tilt, Zoom, Focus, Brightness, Preset Position, Auto mode (depending on camera model)
 - Audio from the i-PRO network cameras can be recorded and played back, G.726 (ADPCM) 32 kbps.
-
- Flexible Playback Controls: Goto Date (Jump to specific time/date), Goto Last (Jump to 30 s before the record end)
 - Various Display Modes: Spot, Multiscreen (4 / 16 split screen display, 3 / 4 / 6 / 9 / 12 / 16 split screen display on a full screen)
 - Various Recording Modes: Schedule, Event (Pre/Post)
 - Filtered Search: Time & Date, Event Type, Camera number, Timeline
 - Recorded images can be downloaded to a PC.

- Downloadable viewer software allows playback of images downloaded from the Recorder.
- Built-in network interface (10Base-T / 100Base-TX / 1000Base-T) for recording and client access
- Up to 4 clients can monitor image and control WJ-NV200 simultaneously.
- Up to 2 HDDs (3.5 inch Serial ATA) can be installed. (WJ-NV200 only)
- User authentication, 3 user levels and User level - Camera partitioning setup for user management of up to 16 user registrations
- Multi-recorder, Multi-site system can be made with optional WV-ASM200 i-PRO Management Software.
- Onvif NVC (Network Video Client), core spec Ver.1.02 conformant
- DVD drive built-in (WJ-NV200V)

Up to 16 network cameras can be connected and recorded.

H.264, MPEG-4 and JPEG multi format

Real Time Face Matching function by matching registered face images with a face displayed on live images

WJ-NV200

Supported Cameras	Supported Cameras	Panasonic i-PRO series Network cameras Onvif NVT comformant camera and encoder camera
	Supported Image Format	H.264, MPEG-4, MJPEG
	Supported Image Resolution	Aspect ratio [4:3]: SXVGA (1,280 x 960), SVGA (800 x 600), VGA (640 x 480), QVGA (320 x 240) Aspect ratio [16:9]:1,920 x 1,080, 1,280 x 720, 640 x 360, 320 x 180)* Depending on the camera
	Supported Audio Format	G.726 (ADPCM) 32 kbps
	Maximum Number of Cameras	16
Recording	Recording Mode	Event, Schedule
	Pre-alarm Recording	Up to 15 seconds (Up to 10 seconds at 1,920 x 1080 resolution)
	Scheduled Recording Mode	2 programs, 3 time zones/day, Independent setup for each day of the week
	Frame Rate/Camera	Up to 30 ips (Depending on the Camera)
Main Unit Functions	Camera Control	Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode, Click centering, Wheel zoom, Zoom reset, Auto Back Focus
	Multiscreen Mode	4 / 16 split screen display, 3 / 4 / 6 / 9 / 12 / 16 split screen display on a full screen
	Playback Control	PLAY, Rev PLAY, Pause, Stop, FF, FR, Prev Record, Next Record, Prev Image, Next Image, Goto Date, Goto Last (30 s)
	Search Mode	Search criteria: Time date, Playback by designating a timeline, VMD
	Copy	Recorded data of selected cameras and time date range can be copied to the SD (SDHC) card.
	Camera Title	Up to 14 characters
	Clock Display	Time: 12H/24H, Date: 5 formats
	Digital Zoom	Live: 2x, 4x, 8x (only for 1-screen or 4-screen) Play: 2x, 4x, 8x
	System Log	Operator access (100), Network error (100), Error (1,000), Event (750)

	System Setup	Setup page in English, French, Italian, Spanish, German, Russian, Japanese
Browser GUI	Camera Control	Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode, Click centering, Wheel zoom, Zoom reset
	Playback Control	REC, PLAY, Rev PLAY, Pause, Stop, FF, FR, Prev Record, Next Record, Prev Image, Next Image, Goto Date, Goto Last (30 s)
	Search Mode	Search criteria: Time date, Event type, VMD, Camera number
	Display Mode	1 / 4 screen
	Image Download	Recorded data of selected camera and time range can be downloaded to a PC. Viewer software can be downloaded separately.
	Copy	Recorded data of selected cameras and time date range can be copied to the SD (SDHC) card.
	Camera Title	Up to 14 characters
	Clock Display	On the browser. Time: 12H/24H, Date: 5 formats
	Digital Zoom	Live/Play: 2x, 4x (only for 1-screen)
	System Log	Operator access (100), Network error (100), Error (1,000), Event (750)
	GUI Language	English, French, Italian, Spanish, German, Russian, Japanese
	Supported OS and Browser Combination	Microsoft® Windows® 7 Professional 64 bit/32 bit & Windows® Internet Explorer® 8.0, Microsoft® Windows Vista® Business SP1 32 bit & Windows® Internet Explorer® 7.0, The language of OS must be the same as selected GUI language.
	Required PC	MJPEG/MPEG-4
H.264		CPU: Intel® Core™ i7-920 or faster, RAM: 3 GB or more, VRAM: 128 MB or more (Min. 64 MB), Microsoft® DirectX® 9.0c or later
Alarm/Event	Alarm Source	9x Terminal inputs, 16x Camera alarms, Panasonic Alarm Protocol
	Face Matching	Off / On
	Event Mode	Off / On
	Alarm Action	Alarm recording, e-mail notification, Alarm

		message, Camera positioning, Terminal output, Panasonic alarm protocol output, Buzzer, Indicator	
	Alarm Control	Reset	
	Event Log	750	
Input / Output	Spot Output Connector	1x 1 V [p-p] / 75 Ω (BNC)	
	Monitor (HDMI) Connector	1x HDMI	
	Audio Output Connector	1x -10 dBv, 600 Ω, Unbalanced (RCA)	
	Alarm/Control Connector (25pin D-sub)	Alarm	Alarm input 1 ~ 9*1, Alarm output*2, Alarm reset input*1, Face matching output*2
		Control	Time adjustment input*1, +5 V output*3
		Error/Warning	Network error output*2, HDD error output*2, Camera error output*2, Recorder error output*2, Recording error output*2
		Mouse Connection Port	1x
		Network Port	1x 10BASE-T / 100BASE-TX / 1000BASE-T (RJ-45)
		SDHC/SD Memory Card Slot	SDHC/SD memory cards applicable (miniSD cards and microSD cards not applicable)
Network	Maximum Bandwidth	Total 80 Mbps or less	
	Supported Protocol	TCP/IP, UDP/IP, HTTP, FTP, SMTP, DNS, NTP, SNMP, RTP	
	E-mail	Upon Alarm or Warning	
	No. of Simultaneous Users	4 or less	
	User Registration	Up to 16 users	
	User Level	3 Levels (Programmable)	
	Partitioning	User level - Camera (View & Control, No Access)	
	Security Method	User authentication (ID and Password), Alteration detection	
Other Functions	Time Synchronization	Terminal (Slave), NTP (Server/Client)	
	Summer Time	User definable (using menu setup)	
HDD	Type	WJ-NV200: 8.89 cm (3.5 inch) Serial ATA HDD, Up to 2x HDDs can be installed. WJ-NV200V: 8.89 cm (3.5 inch) Serial ATA HDD Up to 1x HDD can be installed.	
	DVD *WJ-NV200V only	Supported DVD disk type	DVD-R, +R (Not supported : DVD-R DL, +R DL, DVD-R for authoring. 8 cm disks)
Viewer Software	Playback Control	Play, Rev Play, Pause, FF, FR, Prev Record,	

		Next Record, Prev Image, Next Image
	Additional Functions	Alteration detection, Save as JPEG, Two times zoom, Print, Copy
	Supported OS, Language	Same as browser GUI, Language of the software will be English
General Specifications	Safety/EMC Standard	UL (UL60065), FCC (Part15 ClassA), C-UL (CAN/CSA C22.2 No.60065), DOC (ICES003 ClassA)
	Power Source	120 V AC, 60 Hz
	Power Consumption	approx. 45 W
	Ambient Operating Temperature	Main body: +5 °C ~ +45 °C (41 °F ~ 113 °F), Mouse (provided): +5 °C ~ +40 °C (41 °F ~ 104 °F)
	Ambient Operating Humidity	WJ-NV200 : 5 % ~ 90 % (without condensation) WJ-NV200V : 10 % ~ 80 % (without condensation)
	Maximum Operating Altitude	2,000 m (6,562 feet) above sea level
	Dimensions	420 mm (W) x 88 mm (H) x 300 mm (D) (16-17/32" (W) x 3-15/32" (H) x 11-13/16" (D)) (excluding rubber feet and projections)
	Mass (approx.)	4.8 kg (10.6 lbs.) without HDD 5.6 kg (12.36 lbs.) with 1 HDD 6.4 kg (14.13 lbs.) with 2 HDDs (WJ-NV200 only)
	NOTE	*1: Non-voltage make contact input, 50 kΩ +5 V DC pull-up *2: Open collector output, 24 V DC, 100 mA max. *3: 200 mA max.