



KX-MB2170 FAX PANASONIC

| | | KX-MB2177 | KX-MB2170 |
|--------------------------------|---------------|---|--------------|
| General | | | |
| Printing Process | | Laser | |
| Recording Paper Size (Simplex) | | -Input Tray: A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K -Manual tray: A5, A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K, Envelope #10/DL/YOUKEI #4/CHOUKEI #3/CHOUKEI #4, Custom (W: 210-216 mm, L: 279-356 mm) | |
| Recording Paper Capacity*1 | | Max: 251 sheets [Standard input tray: 250 sheets / Manual tray: 1 sheet] | |
| Paper Output Capacity | | 100 sheets | |
| ADF | Capacity | 35 sheets | |
| | Document size | A4, A5, LTR, LGL, B5(JIS), B5(ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K | |
| LCD Display | | 16 digits / 2 lines with back-light | |
| Memory Size | | 128 MB | 64 MB |
| Monthly duty | Average | 1,200 pages | 1,200 pages |
| | Maximum | 30,000 pages | 12,000 pages |
| Power Consumption | | Maximum: Approx. 1000 W Copy: Approx. 500 W, Ready: Approx. 65 W Sleep: Less than 3.3 W*2 | |
| Noise level | Standby | Less than 25 dBA*3 | |
| | Copying | Less than 52 dBA*3 | |
| Computer Interface | | Wi-Fi (IEEE802.11b/g/n), 100Base-TX/10Base-T, USB2.0 | |
| Dimensions (W x D x H) | | 410 x 400 x 320 mm (Including handset: 447 x 400 x 320 mm) | |
| Weight | | Approx. 12 kg | |
| Printer | | | |

| | | |
|--------------------------|--|---------------------|
| Print Speed | Up to 26 ppm (A4) | |
| Duplex Printing | Yes (A4, LTR, LGL, 216 x 330 mm, 216 x 340 mm) | |
| Duplex Productivity (A4) | 92 % (24 ppm) | |
| Print Resolution | Up to 2400 x 600 dpi | Up to 600 x 600 dpi |
| First Print Time | 8.5 s (from standby) | |
| Emulation | GDI | |
| Supported OS | Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows Server® 2008, Windows Server® 2012, Mac OS X 10.5 - 10.10*4, Linux®*5 | |
| Copier | | |
| Copy Speed *6 | Up to 26 cpm (A4) | |
| Copy Resolution | Up to 600 x 600 dpi | |
| Multi-Copy | 99 pages | |
| First Copy Time | Approx. 10.5 s (ADF) | |
| Reduction / Enlargement | 25 % - 400 % (1 % step) | |
| Copy Function | Quick ID, N-in-1, Separate N-in-1, Poster, Image Repeat, Booklet, Edge/Margin | |
| Scanner | | |
| Color / Mono Scan | Yes / Yes | |
| Scan Resolution | Optical: Up to 600 x 1200 dpi (Flatbed) / Interpolated: Up to 19200 x 19200 dpi | |
| Scan Function | Scan to PC / Email Address / FTP / SMB | |
| Supported OS | Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Mac OS X 10.5 - 10.10*4, Linux®*5 | |
| Fax | | |
| Modem Speed | 33.6 kbps - 2.4 kbps with automatic fallback | |
| Memory Size | Total 3 MB (Reception: Approx. 80 pages*7, Transmission: Approx. 150 pages*7) | |
| Address book | 100 | |
| Fax / Tel Switch | Yes | |
| Fax to Email | Yes | |
| Web Fax Preview | Yes | |

*1 Depending on the type of paper.

*2 When only USB interface is connected and LAN is OFF mode. Power consumption in sleep mode depends on machine condition.

*3 Sound Pressure Level based on ISO7779 bystander position. It depends on the measuring method.

*4 Mac OS X 10.10 driver is provided via web download.

*5 Supported Linux distribution: Red Hat® Enterprise Linux® Desktop 5/6/7, Ubuntu® 10/11/12/13/14. Driver is provided via web download.

*6 Continuous copy of a single original.

*7 Based on the ITU-T No. 1 Test Chart in standard resolution.

- Windows, Windows Vista, Windows Server are registered trademarks of Microsoft Corporation in the United States and/or other countries.

- Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries.
- Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.
- Red Hat and Red Hat Enterprise Linux are registered trademarks or trademarks of Red Hat, Inc. in the United States and/or other countries.
- Ubuntu is a registered trademark or a trademark of Canonical Ltd. in the U.S. and other countries.