

KX-TS580MX / KX-TS560MX / KX-TS520MX

Integrated Telephone System

The KX-TS580MX and KX-TS560MX Equipped with Handy Features, Including Both LCD Display and Caller ID

*2 RoHS-specified No Chemical Used substances Lead, cadmium, mercury, hexavalent chromium and specified brominated flame retardants (PBB and PBDE).



Outstanding Features with Built-In Quality

Caller ID Compatible

The KX-TS580MX / KX-TS560MX are suitable for Caller ID service. The 2-Line LCD displays caller S name (required registration in phonebook) and number.
You can know who S calling before you answer.
Except KX-TS520MX.

Requires subscription to Caller ID service by a telephone company.

Phonebook (50 Entries)

Up to 50 numbers and names can be stored in its phonebook. You can make a call by selecting a name or number from the phonebook.

Except KX-TS520MX.

Ringer Indicator

You can confirm incoming calls visually. Ringer Indicator flashes to indicate there is an incoming call.
Convenient when waiting for a call.

Specifications	KX-TS580MX	KX-TS560MX	KX-TS520MX
	Black White	Black White	Black White Red
General			
Number of Line	1	1	1
Data Port	✓	√ _	✓
One Touch Dial	×	×□	3
Redial Memory	20-Station	20-Station	Last One
Auto Redial	✓	×	×
One Touch Redial	I (Last One)	I (Last One)	I (Last One)
Phonebook Name Input	English (50 Entries)	English (50 Entries)	×
One Touch Tone Switchin		✓	✓
/ Tone Setting	Programmable	Programmable	Switchable
Pulse / Tone Default	Tone	Tone	Tone
Flash Time	Programmable	Programmable	600 ms Fix
Flash Time Default	600 ms	600 ms	×
Insertable Pause	3.5 s	3.5 s	2.1 s
Ringer Volume	Off / Low / High	Off / Low / High	Off / Low / High
Ringer Indicator	√	✓	✓
Electronic Hold	√	×	×
Electronic Hold on Music	√	*	×
Speakerphone	√	*	×
Speakerphone Volume	8-Step	*	×
Mute	√	√	x
On-Hook Dialing	√	√	×
Handset Receiver Volume	· ·	4-Step	6-Step
Call Restriction	Programmable (0 or Up to 2 digits)	Programmable (0 or Up to 2 digits)	×
Dial Lock	√	√	x
Navigator	✓	✓	×
LCD	D + 46 l' '' 76 - 0 l' '' + D' +	D + 16 lb 2 7 5 0 lb 2 4 18 1	×
LCD	Dot x 16 digits 7-Seg x 8 digits + Pict	Dot x 16 digits 7-Seg x 8 digits + Pict	×
LCD Language (Menu Sele		English only	×
	4-Step	4-Step	*
Caller ID Compatible	√	√	×
Signal	FSK&DTMF	FSK&DTMF	×
Private Name Display	ו (Required Registration in Phonebook)	I (Required Registration in Phonebook)	×
Caller ID Memory	50-Station	50-Station	×
Time / Day Stamp from CI		50-5tation √	×
Voice Mail (FSK)	V ✓	· ·	×
Others			
Power Source	3 x AA and Line	3 x AA and Line	Line
Wall Mountable	√ Valid Ellic	√ √	√
Dimensions W x D x H (mr		190 x 196 x 95	190 x 196 x 95
Weight (g)	685	665	518
11019110 (9)	003	003	310

