

# Panasonic



**Call**

**2LINE**

**INTERCOM**



**HEADSET-READY**

Headset Jack (Headset Optional)

## KX-TS3282BX

*Advanced* **ITS**

**IDEHAL**  
Gostar



# INTEGRATED TELEPHONE SYSTEM

# KX-TS3282BX *Advanced ITS* 2LINE

## Outstanding Features with Built-In Quality

### 2-Line Operation

The 2-line system lets you speak on one line, and still make and receive calls on the other.

### 3-Way Conference Calling

You can enjoy 3-way conversations with two separate parties on both lines by using the conference button.

### One Intercom Path

Allows you to page any phone individually or all simultaneously and to communicate with an internal call.

### Caller ID Compatible (FSK/DTMF)\*

KX-TS3282BX is suitable for each technical standard of Caller ID service (Bellcore, ETSI and DTMF). The 3-Line LCD displays caller's information.

### 50-Station Caller ID Memory\*

Up to 50-Station can be stored, you can call back easily.

### 50-Station Phone Directory

Up to 50 names and telephone numbers can be stored.

### Answer-Back Speakerphone

Allows you to activate the speakerphone by remote from other KX-TS3282BX.

### Programmable Line Selection

You can program one of 4 operational modes (line 1/2/Intercom/Auto).

### Flexible Extension Numbering

You can easily assign specified extension numbers to each intercom.

\*Requires subscription to Caller ID service offered by certain telephone companies for a fee. Please check with local Telephone Company for details and availability.

## Additional Features

- 3-Station One-Touch Dialer
- Auto Redial with Redial Memory
- Parallel Connections Up to 8 Extensions
- Data Port
- Call Transfer
- Distinctive Ringing
- Call Restriction
- Dial Lock
- User Programmable Timed Flash (80/90/100/110/200/250/300/400/600/700 ms)
- Telephone Line-Powered Operation
- Headset Jack
- Power Failure Battery Backup Battery Box
- Navigator Key for Easy Operation

## Specifications

Dial Mode:	Tone (DTMF)/Pulse	Power Source:	AC Adaptor
Pause:	3.5 sec	Dimensions (HxWxD):	96 mm x 186 mm x 231 mm
Flash:	User-programmable	Weight:	890 g

**Panasonic** **IDEHAL**  
Gostar

Design and specifications are subject to change without notice.  
0.1M1202SK-TS3282BX-ML Printed in Japan